



USAI® Lighting

the LittleTwos™

APPLICATION GUIDE





Introducing the LittleTwos™

Small, powerful and quiet runs in this **Tier Two** family of 2" aperture pinhole and 2" diameter cylinder light fixtures. Providing incredible performance with advanced glare control for visual comfort, the complete family offers an expansive range of options for trim styles, trim configurations, beam spreads, housings and more.

This lighting toolbox of options gives specifiers a great deal of flexibility in a 2" fixture. Use **the LittleTwos application guide** as a reference for useful technical information to leverage this comprehensive collection in built environments of all types and sizes.

CONTENTS

the LittleTwos Pinhole

Features & Configurations
Optics
Installation & Housings Options
Drivers & Enclosures

03-08

the LittleTwos Cylinder

Features & Configurations
Hang Straights
Drivers & Enclosures

09-12

the LittleTwos

LED Color Choices & Performance

13

Applications

Lobby
Open Office
Airport
Residential
Corridor
Restaurant
Retail

15-30

Related Products & FAQs

31

the LittleTwos™ Pinhole

High Performance Features and Specifications

TIER 2
\$ \$ \$

THE POWER
Up to 2000 Delivered Lumens*

TRIMMED

2" 2"

TRIMLESS

2" 2"

FUNCTIONS



Standard Regress Downlight



Deep Regress Downlight




Adjustable



Wall Wash





HOUSING

The LittleTwos Pinhole offers new construction and install from below housing options for easy installation in any site condition. Always serviceable from below, select from options to install from above or below the ceiling.

- Install from Below:**
- Retrofit, Flex Driver Case
- New Construction Installation, Service from Below:**
- New Construction Tray (NCT)
 - Insulation Contact and Chicago Plenum Housings (NCIC, NCCP)
- New Construction Installation, Service from Above:**
- New Construction Above Ceiling Access Housing (ABC)

- LED COLOR OPTIONS**
- Classic White® – 80+ and 90+CRI
 - Dim-to-Warm – 90+ CRI
 - Dim-to-Warm + – 90+ CRI
 - Color Select® Tunable White – 90+ CRI


- LISTINGS**
- IBEW Union Made
 - Meets WELL Building Standards
 - 0.1% Dimming Options
 - Dry, Damp, Wet Locations
 - 5 Year Warranty
 - Buy American Act Compliant
 - CSA-US Listed
 - T24/JA8*
 - Declare Label Red List Approved*



2"

the LittleTwos™ Trim Matrix


Choose from a variety of trim options and combinations. The LittleTwos Recessed Pinholes are available in trimmed, trimless, and millwork, round or square, downlight, deep regress downlight, adjustable, and wall wash. A selection of finishes are available along with options perfect for visually quiet ceiling integrations.

	Trimmed	Trimless	Millwork
Round Downlight			
Square Downlight			
Round Comfort Downlight			
Square Comfort Downlight			
Round Adjustable			
Square Adjustable			
Round Wall Wash			
Square Wall Wash			

- FINISH OPTIONS**
- White Matte
 - Black Matte
 - Silver Matte
 - Black Specular

the LittleTwos™ Pinhole Optics

Standard Regress Downlight




Spacing Criterion*

20°	25°	30°	50°	65°
0.38	0.42	0.54	0.80	0.96

*Spacing criterion is an estimated maximum spacing to mounting height ratio to produce acceptable uniformity on the workplane.

Deep Regress Downlight



What is UGR?


UGR = Unified Glare Rating, a measure of the discomfort glare produced by a light fixture. Best practices recommend to use lighting fixtures with UGR < 19

About Cutoff

The cutoff angle is the lowest angle going up from nadir at which you do not have a direct view of the light source. Lower cutoff angles are better for glare control.


KEY

- A Thermal management engineered for premium light quality over fixture lifetime
- B Mounting wings
- C Highly efficient LED light engine with 2-step MacAdam ellipse color consistency
- D Native Optic
- E Trim Fitting
- F Optic Holder
- G Adjustment Mechanism with Tilt Angle Indicators
- H Optic Media & Accessories
- I Accessories Holder
- J Trim



LENSES AND ACCESSORIES


Linear
Filters
Spread Lens
Hexcell Louver
Color Shifting (CTO)



Installation & Housing Options

Integral Drivers


Retrofit Installation



1. Insert Flex Driver Case from Below Ceiling Plane
2. Flex Driver Case Automatically Drops to 90° Angle and Reduces Plenum Height Requirements
3. Finished Installation from Below with Integral Driver

New Construction Installation

SERVICE FROM BELOW:




NCT can be specified as an accessory to RT flex driver case fixtures. 6-3/4" plenum height required for driver.

SERVICE FROM ABOVE:



Insulation Contact and Chicago Plenum Housings (NCIC, NCCP)



New Construction Above Ceiling Access Housing (ABC)

Remote Drivers

Remote drivers can be provided with mounting plates, single driver enclosures, or in pre-wired, big-box enclosures for multiple drivers upon request. USAI applications and quotes teams can assist with the optimization of remote driver layouts and configurations for the best possible price for your project. USAI's the LittleTwos are compatible with all common lighting controls. Choose from 0-10V, Phase, EcoSystem, DMX, or DALI dimming.

2 Ways To Work With Remote Dimming Drivers


1 Standard Output with 2+ Multiple Fixtures Per Driver

Connect up to four light fixtures at a time to one dimming driver for efficient power distribution and cost savings.



2 High Output with 1 Fixture Per Driver

Dedicating one fixture per driver provides optimal performance and best possible delivered light output



Optional USAI Enclosures

All remote drivers require enclosures by code. We make your specification process easier by offering different driver enclosures to fulfill all of your project needs.

Single Driver Enclosure Options

For one remote driver at a time only.



ENC Single Driver Enclosure



MP Junction Box Mounting Plate Enclosure

Prewired Enclosures by USAI

Enclosures can house up to 12 dimming drivers.



the LittleTwos™ Cylinder

High Performance Features and Specifications

TIER 2
\$ \$


THE POWER
Over 1000 Delivered Lumens*

FUNCTION:



APERTURE & SHAPE
2" Round x 4" Height

BEAM SPREADS



- LED COLOR OPTIONS**
- Classic White® – 80+ and 90+CRI
 - Dim-to-Warm – 90+ CRI
 - Dim-to-Warm + – 90+ CRI

- LISTINGS**
- IBEW Union Made
 - Meets WELL Building Standards
 - 0.1% Dimming Options
 - Dry, Damp, Wet Locations
 - 5 Year Warranty
 - Buy American Act Compliant
 - UL Listed
 - T24/JA8*
 - Declare Label Red List Approved*

* Coming Soon

Actual Size



2', 4', 6' and 8' suspension lengths are field adjustable

Cable Mount

4"

2"

the LittleTwos™ Cylinder

	DOWNLIGHT			ADJUSTABLE		WALL WASH	
	Surface	Pendant Cable	Pendant Stem	Surface	Pendant Stem	Surface	Pendant Stem
Remote Driver 2" Canopy							
Recessed or Remote Driver 5" Canopy							
Remote Driver Conduit Cutout							
Canopy Mounted Driver 5" Canopy							
Canopy Mounted Driver Conduit Cutout							

FINISH OPTIONS

Inner Baffle


- White
- Conduit Silver
- Grey
- Black
- Bronze
- Clear Matte
- Piano Gloss Black
- Custom RAL#

Body, Canopy and Stem

- White
- Conduit Silver
- Grey
- Black
- Bronze
- Custom RAL#


Mounting Type

Choose the best option for your ceiling installation.




Surface Mount

The lowest profile installation possible, completed with no visible hardware.



Cable Mount

1/8" Ø high-tension shielded conductor cable is silver in color and can be adjusted in the field to desired length.




Pendant Stem Mount

3/8" Ø steel stem is provided in a powdercoat painted finish with either a 10° hang straight or a 30° hang straight. Hang straight details are shown below.


Hang Straight Options

Available with Pendant Stems Only

10° Hang Straight



30° Hang Straight



3 ways to stash your drivers

USAI's the LittleTwos are compatible with all common lighting controls. Choose from 0-10V, Phase, EcoSystem, DMX, or DALI dimming.

1 Recessed Rough-In Driver Enclosure

USAI offers recessed rough-ins which allows for placement of drivers in the ceiling at the light fixture location. Recessed rough-ins act as enclosures for drivers which can be accessed and serviced through the rough-in aperture behind the cylinder canopy.



Recessed Driver

- 5" Canopy
- High Output with 1 Fixture Per Driver

2 Canopy Mounted Drivers

USAI offers two driver canopy solutions – one for use with recessed junction boxes, and a driver canopy for use with surface mounted junction boxes.



Canopy Mounted Driver

- 5" Canopy
- High Output with 1 Fixture Per Driver



Canopy Mounted Driver

- Conduit Cutout Canopy
- High Output with 1 Fixture Per Driver

3 Remote Driver and Enclosures

For the remote drivers, you can use either 1 fixture per driver or multiple fixtures per driver (Max of 4 fixtures). Depending on your output preference.

Optional USAI Enclosures

All remote drivers require enclosures by code. We make your specification process easier by offering different driver enclosures to fulfill all of your project needs. See page 8 for more information.



Remote Driver

- 2" Canopy
- High Output with 1 Fixture Per Driver
- Standard Output with 2+ Multiple Fixtures Per Driver




Remote Driver

- Conduit Cutout Canopy
- High Output with 1 Fixture Per Driver
- Standard Output with 2+ Multiple Fixtures Per Driver


the LittleTwos™ LED Color Choices


Light is equally as precious as the finishes and materials in a room. Every space, object, or task has an ideal shade of light to be lit by. Choosing the right light can make everything, everyone, and the experience extraordinary. Offering white color temperatures ranging from 2200K to 6000K, the LittleTwos are available with **Classic White**, **Dim to Warm**, **Dim to Warm +**, and **Color Select Tunable White**. Choose the USAI LED color option(s) that's best for your next project.

 **Classic White®**
2700K, 3000K, 3500K, 4000K, 80+ and 90+ CRI





2700K DAY







3000K DAY






3500K DAY







4000K DAY




 **Dim-to-Warm, and Dim-to-Warm + 90+ CRI**
3000K - 2000K and 3000K - 1800K at 90+ CRI



100% INTENSITY AT 3000K



18% INTENSITY AT 2200K

 **Color Select® Tunable White**
6000K-2200K, Tunable White Light 90+ CRI



3600K, 80% INTENSITY



4800K, 70% INTENSITY






2400K, 50% INTENSITY



the LittleTwos™ Pinhole Performance Data

Small, Powerful, Quiet and Flexible.

	<div> Classic White 2700K, 3000K, 3500K, 4000K 80+ and 90+ CRI</div>					<div> Dim-to-Warm 3000K-1800K 90+ CRI Dim-to-Warm + 3000K-2000K 90+ CRI</div>	<div> Color Select Tunable White 6000K-2200K 90+ CRI</div>
Wattage	7W	9W	11W	15W	20W*	15W	15W
Source Lumens	800	1200	1125	1875	2600	1100	1000
Maximum Delivered Lumens	725	900	1025	1400	2000	800	775



the LittleTwos™ Cylinder Performance Data

Come for the power. Stay for the comfort.

	<div> Classic White 2700K, 3000K, 3500K, 4000K 80+ and 90+ CRI</div>				<div> Dim-to-Warm 3000K-1800K, 90+ CRI Dim-to-Warm + 3000K-2000K, 90+ CRI</div>
Wattage	7W	9W	11W	15W	15W
Source Lumens	800	875	1125	1275	1100
Maximum Delivered Lumens	550	700	800	1050	600

* Coming Soon




Make your design a reality with the LittleTwos™

Layer in your specifications with the LittleTwos™. This 2" family's vast offering provides an abundance of possibilities. The following pages are filled with inspirational application illustrations and helpful technical information to help turn specifiers' designs and concepts into a reality. Use these pages as a resource and let your creativity take the lead. **Get TWO It!** →

Lobby 18' Ceiling

DESIGN GOAL: Create a well-lit and inviting atmosphere in a lobby with a high ceiling that allows occupants to navigate through the space intuitively. Utilize an efficient lighting scheme to achieve the average IES recommended light levels on all surfaces.



LAYER A SPECIFICATION:

Fixture Spec: CLRD4-07V4C-35KH-15-WH
Mounting Height: 7FT
Beam Angle: 15°
Wattage: 7W
Color Temperature: 3500K, 90+ CRI
Delivered Light: 504 Lumens
Glare (UGR): 11.7



LAYER B SPECIFICATION:


Fixture Spec: S2RD-15V2M-35KH-30-P1-WH
Mounting Height: 18FT
Beam Angle: 30°
Wattage: 15W
Color Temperature: 3500K, 90+ CRI
Delivered Light: 1382 Lumens
Glare (UGR): 16



Smooth Transitions

SOLUTION: To meet the design goal, the lobby uses two layers of lighting. **Layer A, Cylinder** is placed 2’ on center to highlight the reception desk and provide adequate task lighting. **Layer B, Downlights** are used in an 8’x8’ spacing to provide even ambient illumination in this 18’ ceiling space. The lighting calculation below illustrates that this layout delivers over 110 footcandles on the work plane and over 17 footcandles on the floor. This design provides light levels that allow occupants to navigate intuitively through the lobby.

FLOOR PLAN: ○ A.Cylinder ● B.Downlight



LIGHTING INTENSITY

Avg On Floor: 17.15 FC
Max/Min: 3.83


Avg On Reception Desk: 114 FC
Max/Min: 3.13

Room Dimension:
30’W x 60’L x 18’H


Table Dimension:
2’W x 10’L x 3’-6”H

NOTE: Light level calculations reflectance values use standard 20% for floors, 50% for walls, and 80% for ceilings.

15° Beam Distribution




30° Beam Distribution



Open Office 9' Ceiling

DESIGN GOAL: Formulate an open office lighting design that provides sufficient light levels for productive work while at the same time minimizing glare for employees’ visual comfort. Utilize an efficient lighting scheme to achieve the average IES recommended light levels on all surfaces.



LAYER A SPECIFICATION:

Trimmed Square Downlight

FIXTURE SPEC: S2SD-15V2M-30KS-65-P1-BG


BEAM ANGLE: 65°

WATTAGE: 15W

COLOR TEMPERATURE: 3000K, 80+ CRI

DELIVERED LIGHT: 906 Lumens

GLARE (UGR): 18



LAYER B SPECIFICATION:

Trimmed Square Wall Wash

FIXTURE SPEC: S2SW-15V2M-30KS-W1-D1-SG

BEAM ANGLE: Wall Wash

WATTAGE: 15W

COLOR TEMPERATURE: 3000K, 80+ CRI


DELIVERED LIGHT: 830 Lumens



Lighting for Productivity

SOLUTION: Two layers of lighting are used to meet the design goal. **Layer A, Downlights** spaced 6'x 6' apart, achieve 44 footcandles on the work plane and 28 footcandles on the floor. This lighting layer provides even illumination for circulation and plenty of illumination for computer work, paperwork, and more. **Layer B, Wall Wash** spaced 3' away from the wall and 3' apart, achieves 21 footcandles on the wall. This lighting layer can be used to highlight artwork, graphics, or any vertical wall surface to create visual interest.

FLOOR PLAN: ■ A.Downlight ■ B.Wall Wash



WALL WASH FOR THE BACK WALL



LIGHTING INTENSITY

Avg On Floor: 28.52 FC
Max/ Min: 5

Avg On Desk: 44 FC
Max/ Min: 1


Avg On Back Wall: 21.31 FC
Max/ Min: 2.9

Room Dimension:
50'W x 30'L x 9'H


Table Dimension:
4'W x 10'L x 2'-6"H

NOTE: Light level calculations reflectance values use standard 20% for floors, 50% for walls, and 80% for ceilings.

65° Beam Distribution




Wall Wash Distribution



Airport 25' Ceiling

DESIGN GOAL: Typical airport terminals are voluminous spaces, with high ceilings and broad open areas. The intent is to utilize a low-glare ambient lighting scheme to achieve the average IES recommended light levels, create a sense of space, and guide traffic flow in the Airport terminal interior spaces.



LAYER A SPECIFICATION:

Trimmed Round Downlight


- FIXTURE SPEC: S2RD-15V2M-40KH-30-P1-WH
- BEAM ANGLE: 30°
- WATTAGE: 15W
- COLOR TEMPERATURE: 4000K, 90+ CRI
- DELIVERED LIGHT: 1199 Lumens
- GLARE (UGR): 15.5



Small and Powerful

SOLUTION: The design strategy uses one layer of lighting to meet the design goal. **Layer A, Downlights** are spaced 8'x 8' apart and achieve 44 footcandles on the work plane and 24 footcandles on the floor. This lighting layer provides plenty of illumination for circulation, service stations, and any signage on the walls for wayfinding to retail shops.

FLOOR PLAN



LIGHTING INTENSITY

Avg On Floor: 22.53 FC
Max/Min On Floor: 3.46

Avg On Desk: 38 FC
Max/Min On Desk: 1


Avg On Wall: 6.57 FC
Max/Min On Desk: 5

Room Dimension:
200'W x 400'L x 25'H

Table Dimension:
15'W x 2'L x 3'H


NOTE: Light level calculations reflectance values use standard 20% for floors, 50% for walls, and 80% for ceilings.

30° Beam Distribution



Residential 12' Ceiling

DESIGN GOAL: Incandescent lighting is the most familiar and comforting light source for residential spaces because of the warm color temperature. Our intent is to utilize an efficient lighting scheme to provide a beautiful, dim to warm lighting experience with energy efficient LEDs and still achieve the average IES recommended light levels.



LAYER A SPECIFICATION:
Trimless Round Adjustable

FIXTURE SPEC: S2RA-15DW2-3020KH-65-WH
BEAM ANGLE: 65°
WATTAGE: 15W
COLOR TEMPERATURE: 3000K, 90+ CRI
DELIVERED LIGHT: 577 Lumens
GLARE (UGR): 22.8

LAYER B SPECIFICATION:
Surface Mount Adjustable Cylinder

FIXTURE SPEC: CLRD4-15DW2-3020KH-25-S-WH
BEAM ANGLE: 25°
WATTAGE: 15W
COLOR TEMPERATURE: 3000K, 90+ CRI
DELIVERED LIGHT: 603 Lumens
GLARE (UGR): 20.6

LAYER C SPECIFICATION:
Pendant Cylinder with Glow Glass


FIXTURE SPEC: CLRD4-15DW2-3020KH-25-G1-WH
BEAM ANGLE: 25°
WATTAGE: 15W
COLOR TEMPERATURE: 3000K, 90+ CRI
DELIVERED LIGHT: 603 Lumens
GLARE (UGR): 20.6

Layer Fixtures for Visual Hierarchy

SOLUTION: The design strategy uses three layers of lighting. **Layer A, Adjustable Downlights**, achieves more than 18 footcandles on the furniture and 16 footcandles on the floor. This lighting layer provides general illumination for the living area and can be aimed toward specific points of interest. **Layer B, Surface Mount Adjustable Cylinder**, achieves more than 42 footcandles on the wall art. **Layer C, the Pendant Cylinder Downlight**, achieves 70 footcandles on the bar top. This lighting layer highlights the bar with decorative glow glass and provides task lighting at the same time.

FLOOR PLAN:

● A: Adjustable Downlight ● B: Surface Mount Adjustable Cylinder ● C: Pendant Cylinder



LIGHTING INTENSITY

Avg On Floor: 16.5 FC
Max/Min: 12

Avg On Bar: 70 FC
Max/Min: 2.54

Avg On Artwork: 42 FC
Max/Min: 1.62


Max/Min: 1.42

Room Dimension:
25'W x 20'L x 12'H


Bar Dimension:
2'W x 8'L x 3'-6"H

NOTE: Light level calculations reflectance values use standard 20% for floors, 50% for walls, and 80% for ceilings.

65° Beam Distribution




25° Beam Distribution



Wayfinding 8' Ceiling

DESIGN GOAL: Provide a uniform and adequate level of light for people to move around safely and create the overall mood and atmosphere for the corridor.



LAYER A SPECIFICATION:

Trimmed Round Downlight

FIXTURE SPEC: S2RD-15W-35KS-65-PO-WH

BEAM ANGLE: 65°

WATTAGE: 15W

COLOR TEMPERATURE: 3500K, 80+ CRI

DELIVERED LIGHT: 904 Lumens


GLARE (UGR): 26.1




Navigating Paths

SOLUTION: The lighting design uses one layer of lighting to achieve the intent of the space. **Layer A, Downlights** are spaced 6'x 6' apart and achieve 18 footcandles on the floor. This lighting layer provides even, shadow-free lighting on the floor, ensuring safe transitions as occupants move through the space.

FLOOR PLAN: ● A:Downlight



ELEVATION




LIGHTING INTENSITY

Avg On Floor: 18.42 FC
Max/Min: 1.4

Room Dimension:
8'W x 40'L x 8'H


NOTE: Light level calculations reflectance values use standard 20% for floors, 50% for walls, and 80% for ceilings.

65° Beam Distribution



Restaurant 10' Ceiling

DESIGN GOAL: The first impression of a restaurant is influenced by its lighting design, which also enhances the dining experience. The design intent is to provide adequate light levels, low glare, and a suitable mood and ambiance.



LAYER A SPECIFICATION:

Trimmed Round Adjustable

FIXTURE SPEC: S2RA-09V2M-27KH-30-BL

BEAM ANGLE: 30°

WATTAGE: 9W

COLOR TEMPERATURE: 2700K, 90+ CRI

DELIVERED LIGHT: 690 Lumens

GLARE (UGR): 1.6



LAYER B SPECIFICATION:

Trimmed Round Adjustable

FIXTURE SPEC: CLRD4-09V2M-27KH-15-BC-WH


BEAM ANGLE: 15°

WATTAGE: 9W

COLOR TEMPERATURE: 2700K, 90+ CRI

DELIVERED LIGHT: 518 Lumens


GLARE (UGR): 11.8



Play of Brilliance

SOLUTION: To achieve the design goal, two layers of lighting are used for the restaurant. **Layer A, Adjustable** downlights are spaced 5'x 5' to achieve 20 footcandles on the floor evenly, and 30 footcandles on the dining tables. **Layer B, Cylinders** are spaced 3' apart and provide 57 footcandles along the bar surface. This lighting layer provides intimate lighting for the guests in this area. The fixtures can be zoned separately for flexibility and control of brightness levels to create the desired mood from section to section.

FLOOR PLAN: A: Adjustable B: Cylinder



LIGHTING INTENSITY

Avg On Floor: 20 FC
Max/Min: 17

Avg On Bar: 57 FC
Max/Min: 5.75

Avg On Table: 30 FC
Max/Min: 1


Room Dimension:
23'W x 40'L x 10'H

Table Dimension:
2.3 Diameter x 2'-3"H


Bar Height:
3'-8"H

NOTE: Light level calculations reflectance values use standard 20% for floors, 50% for walls, and 80% for ceilings.

30° Beam Distribution




15° Beam Distribution



Amenity & Retail 10' Ceiling

DESIGN GOAL: Use a lighting scheme to create a welcoming and relaxing atmosphere for the reception area. Create visual attention within the retail section with the intention to attract customers and increase product sales.



LAYER A SPECIFICATION:
Adjustable Pendant Cylinder

FIXTURE SPEC:
CLRA4-07V4C-35KS-20-WH
BEAM ANGLE: 20°
WATTAGE: 7W
COLOR TEMPERATURE: 3500K, 90+ CRI
DELIVERED LIGHT: 427 Lumens
GLARE (UGR): 14.9



LAYER B SPECIFICATION:
Millwork Round Adjustable

FIXTURE SPEC:
S2RA-09V2M-35KH-20-PO-BL
BEAM ANGLE: 20°
WATTAGE: 9W
COLOR TEMPERATURE: 3500K, 90+ CRI
DELIVERED LIGHT: 684 Lumens
GLARE (UGR): 2.8




LAYER C SPECIFICATION:
Millwork Round Adjustable

FIXTURE SPEC:
S2RA-09V2M-35KH-30-PO-BL
BEAM ANGLE: 30°
WATTAGE: 9W
COLOR TEMPERATURE: 3500K, 90+ CRI
DELIVERED LIGHT: 738 Lumens
GLARE (UGR): <1

Focal Glow

SOLUTION: The lighting strategy uses three layers of lighting to meet the design objectives. **Layer A, Adjustable Pendant Cylinder** spaced 3' apart over the reception desk, provides 35 footcandles on that surface. **Layer B and C Adjustable** downlights with 20° & 30° beam distributions are spaced 6'x 6' on center to achieve 74 footcandles on the display cases and 18 footcandles on the lounge tables. The LittleTwos recessed adjustable downlight is an excellent choice for this purpose; the range of beam spread options allows light to be focused on specific product displays or seating areas without glare, yet still provides a cozy environment for clients. The recessed lighting shown here is installed with a millwork trim to blend seamlessly with the millwork ceiling materials.

FLOOR PLAN:
○ A: Adjustable Pendant Cylinder
● B: Adjustable Downlight 20°
● C: Adjustable Downlight 30°



LIGHTING INTENSITY

Avg On Floor: 15 FC
Max/ Min: 12

Avg On Reception Desk: 35 FC
Max/ Min: 5.9

Avg On Table: 18 FC
Max/ Min: 1.3


Avg On Display: 74 FC
Max/ Min: 1

Room Dimension:
23'W x 40'L x 10'H

Table Dimension:
2.3 Diameter x 2'-3"H


Display Dimension:

NOTE: Light level calculations reflectance values use standard 20% for floors, 50%




Better **TWO**gether


USAI Lighting believes in the power of innovating for small, whether it is housings, recessed downlights, or surface mounts and pendants. Mix and match with other USAI high-performance product ranges. Each product has its own set of capabilities with full family offerings to address every design requirement with the greatest flexibility from space-to-space.




the LittleOnes® Zepto® Housing
1" aperture




BeveLED Mini® Basic Pancake™
3" aperture




BeveLED Mini®
3" aperture




the LittleOnes® Zepto®
1"




the LittleOnes® Micro
1.25"




the LittleOnes® Micro Doubles
1.25"




Micro Multi-Cell
1.25" cells



SliverLED®
1.75"



BeveLED Mini®
3"



TrueZero360™
3"

FAQs

Q : How to aim the LittleTwos Pinhole adjustable?

- A :** The adjustable 2" pinhole provides additional flexibility to light spaces with a 360° rotation and a maximum 40° tilt angle while maintaining a quiet below ceiling appearance.
- **Set Rotation:** Insert small flathead screwdriver or hex driver tool into the rotation pocket and push to turn the trim to the desired angle. Rotation is smooth from 0° - 360° and is set and held with friction.
 - **Set Tilt Angle:** Insert hex driver tool into the adjustment screw and turn until desired tilt angle is reached. The screw can be seen easily from below, and tilt angle indicators are visible when the optic is removed.

Q : When should I use an install from below fixture vs new construction housing for the LittleTwos Pinhole?

- A :** Projects with existing ceilings can use the LittleTwos Pinhole Retrofit fixture, which installs from below with a Flex Driver Case to house the dimming driver. This option is available for both trimmed and trimless fixtures.
- Projects that require fixture installations prior to finished ceiling installation can use the new construction tray accessory (NCT) to rough-in light fixture position. The RT fixture with Flex driver case can then be installed from below at a later time.
- Alternatively, we also offer IC and CP rated housings which are both serviceable from below, as well as an Above Ceiling Access only housing (ABC) which is a new construction service from above housing option specifically designed for ACT ceiling types.

Q : How to aim the LittleTwos adjustable cylinder?

- A :** The adjustable 2" cylinder can be surface mounted to the ceiling as a monopoint or suspended by a rigid stem to light spaces with a 360° rotation and a maximum 90° tilt angle.
- **Set Rotation:** Simply turn the cylinder to desired rotation angle, friction will hold the position.
 - **Set Tilt Angle:** This is also a toolless adjustment, simply set the tilt position with your hand and friction will do the rest.

Q : What design challenges can the LittleTwos fixture family address?

- A :** The LittleTwos Pinhole and Cylinder Family offers a wide range of product functions and mounting options – from downlight, deep regress comfort downlight, adjustable, and wall wash, to decorative glow glass options. With a range of wattages and lumen outputs from 500 to 2000 delivered lumens, the LittleTwos product family can be used in a variety of spaces, ceiling types and heights, to fulfill most project needs, including sloped and/or exposed ceiling types.

Q : How can I get help with the project coordination process?

- A :** USAI can help with project challenges and any performance or specification questions. Additionally, USAI offers application assistance to configure remote drivers and remote driver enclosures to streamline the project coordination process. Contact your local USAI representative with your project info and control zone load schedule for help planning driver layouts, power requirements, and custom enclosure configurations.

Q: Which control systems are compatible with the LittleTwos?

- A :** As with all USAI Lighting products, the LittleTwos are compatible with every major architectural controls system, including 0-10V low voltage dimming, line voltage phase dimming, and digital dimming protocols such as DMX and DALI. Wireless dimming controls are available by specifying the Lutron Athena dimming driver option.

Q: Can I place LittleTwos in wet locations such as showers and outdoor covered spaces?

- A :** Yes! The LittleTwos family is dry/damp/wet location rated and can be installed outdoors under covered ceilings.

Q: Can I change the LittleTwos beam spread from below?

- A :** Yes! Optics are field interchangeable. Please refer to the installation instruction and spec sheets optic media page for guidance.

Q: Can I use the LittleTwos to meet my project's code requirements?

- A :** Yes! The LittleTwos Pinhole family is NRTL/CSA-US tested to UL standards, while the LittleTwos Cylinder family is UL listed. All products are IBEW union made and are Buy American Act (BAA) compliant. We offer airtight housing options, as well as Insulation Contact and Chicago Plenum rated housings. The LittleTwos can be used to meet LEED and WELL Building requirements. Title 24 JA8 Certification is underway and Declare Labels with Red List Approved status will be completed soon.

If your project requires something else not listed here, please don't hesitate to contact us!



the LittleTwos™

SMALL, POWERFUL, AND QUIET RUNS IN THE FAMILY



USAI®
Lighting

CALL, EMAIL, OR VISIT [USAILIGHTING.COM](https://usailighting.com) TO LEARN MORE

USAI LIGHTING COLLABORATORY
13 CROSBY STREET
NEW YORK, NY 10013
(845) 234-4090
SHOWROOM@USAILIGHTING.COM

USAI LIGHTING HEADQUARTERS
1126 RIVER ROAD
NEW WINDSOR, NY 12553
(845) 565-8500
INFO@USAILIGHTING.COM

©2024 USAI, LLC. All rights reserved.

USAI, Classic White, Warm Glow, Color Select, the LittleOnes, BeveLED Mini, and BeveLED are registered trademarks of USAI LLC. TrueZero360, and Pancake are trademarks of USAI, LLC. All designs protected by copyright. Covered by US Patents. Patents pending CA-167