



USAI[®] Lighting



Quick Ship

Ships within 10 Days

Tier 1  Budget Friendly



Welcome to USAI Lighting's Quick Ship Program, ensuring delivery within 10 days for orders of 100 pieces or fewer per fixture type.

Ideal for fast-paced, cost-effective projects and applications, our **Tier 1 Primary® NXT** options offer USAI's superior white light in an elegant design. Choose from a selection of Quick Ship offerings including trimmed and trimless designs, available in a white finish in round and square shapes. These recessed lighting fixtures feature high CRI, multiple color temperatures, various beam spreads, and an integral Tri-Mode driver (0-10V/120-277V or forward/reverse phase, 120V) with 1% dimming capability. Integrate seamlessly with other USAI Tier 1, 2, or 3 products to maintain a consistent aesthetic below the ceiling.

Ordering for Quick Ship

1. Quick Ship orders can be placed on the same purchase order as non Quick Ship products.
2. Consult with USAI Lighting for quantities above 100 pieces.



SCAN to Learn More

Recessed



BeveLED Mini® Primary® NXT

FEATURES

3" Aperture

Up to **1175**
Delivered Lumens

Square + Round



Downlight



Wall Wash



Adjustable

Trimmed, Trimless

New Construction
and Insulation Contact
Housing Options

15W

27°, 30°, 50° Beam Options

 **Classic White®**
2700K, 3000K
90+ CRI



T24/JA8

Trimode (0-10V and Phase)
dimming to 1%



BeveLED® 2.2 Primary® NXT

FEATURES


4.5" Aperture

Up to **2025**
Delivered Lumens

Square + Round



Adjustable
Downlight



Wall Wash

Trimmed, Trimless

New Construction
Housing

15W, 20W

20°, 55° Beam Options

 **Classic White®**
3000K, 3500K
90+ CRI

Trimode (0-10V and Phase)
dimming to 1%

3" BevelLED Mini® Primary® NXT

 Dry/Damp/Wet Location Listed Under Covered Ceilings

Primary NXT comes with a Tri-Mode integral driver with 1% dimming. Tri-Mode drivers are compatible with:

1. 0–10V dimming with all voltages from 120V–277V
2. Forward phase or reverse phase dimming with 120V



Downlight

Comes in round or square, trimmed or trimless with a white finish.

Ships with 50° wide beam optic installed; field replaceable 30° medium beam optic included.

Fixture Type	Delivered Lumens	Housing				HSG	Trim Style	Select Color Temp	Trim				Accessory	 Quick Ship
		Wattage	Housing	Voltage & Driver					High CRI	Solite Lens	Trim Finish	Trim		
Round Trimmed	1025	P23U-15M	NCEC	UNV-D22		HSG	P3RDF-L2M	27 or 30	KH	S	WH	TRM	N/A	QS
Round Trimmed, IC Rated	1025	P23U-15M	NCIC	UNV-D22		HSG	P3RDF-L2M	27 or 30	KH	S	WH	TRM	N/A	QS
Round Trimless	1025	P23U-15M	NCEC	UNV-D22		HSG	P3RDL-L2M	27 or 30	KH	S	WH	TRM	P3R-SPAK	QS
Round Trimless, IC Rated	1025	P23U-15M	NCIC	UNV-D22		HSG	P3RDL-L2M	27 or 30	KH	S	WH	TRM	P3R-SPAK	QS
Square Trimmed	1175	P23U-15M	NCEC	UNV-D22		HSG	P3SDF-L2M	27 or 30	KH	S	WH	TRM	N/A	QS
Square Trimmed, IC Rated	1175	P23U-15M	NCIC	UNV-D22		HSG	P3SDF-L2M	27 or 30	KH	S	WH	TRM	N/A	QS
Square Trimless	1175	P23U-15M	NCEC	UNV-D22		HSG	P3SDL-L2M	27 or 30	KH	S	WH	TRM	P3S-SPAK	QS
Square Trimless, IC Rated	1175	P23U-15M	NCIC	UNV-D22		HSG	P3SDL-L2M	27 or 30	KH	S	WH	TRM	P3S-SPAK	QS



Wall Wash

Comes in round or square, trimmed or trimless with a white finish.

Fixture Type	Delivered Lumens	Housing				HSG	Trim Style	Select Color Temp	Trim				Accessory	 Quick Ship
		Wattage	Housing	Voltage & Driver					High CRI	Wall Wash	Trim Finish	Trim		
Round Trimmed	650	P23U-15M	NCEC	UNV-D22		HSG	P3RWF-L2M	27 or 30	KH	D1	WH	TRM	N/A	QS
Round Trimmed, IC Rated	650	P23U-15M	NCIC	UNV-D22		HSG	P3RWF-L2M	27 or 30	KH	D1	WH	TRM	N/A	QS
Round Trimless	650	P23U-15M	NCEC	UNV-D22		HSG	P3RWL-L2M	27 or 30	KH	D1	WH	TRM	P3R-SPAK	QS
Round Trimless, IC Rated	650	P23U-15M	NCIC	UNV-D22		HSG	P3RWL-L2M	27 or 30	KH	D1	WH	TRM	P3R-SPAK	QS
Square Trimmed	825	P23U-15M	NCEC	UNV-D22		HSG	P3SWF-L2M	27 or 30	KH	D1	WH	TRM	N/A	QS
Square Trimmed, IC Rated	825	P23U-15M	NCIC	UNV-D22		HSG	P3SWF-L2M	27 or 30	KH	D1	WH	TRM	N/A	QS
Square Trimless	825	P23U-15M	NCEC	UNV-D22		HSG	P3SWL-L2M	27 or 30	KH	D1	WH	TRM	P3S-SPAK	QS
Square Trimless, IC Rated	825	P23U-15M	NCIC	UNV-D22		HSG	P3SWL-L2M	27 or 30	KH	D1	WH	TRM	P3S-SPAK	QS



Adjustable

Comes in round or square, trimmed or trimless with a white finish.

Ships with 27° TIR optic installed; replacement optics for 20°, 35°, and 50° beams are available on spec sheets with standard lead times.

Fixture Type	Delivered Lumens	Housing						HSG	Trim Style	Solite Lens	Trim Finish	Trim	Accessory	 Quick Ship
		Wattage	Select Color Temp	High CRI	Housing	Voltage & Driver								
Round Trimmed, IC Rated	1075	P3RA-15L2M	27 or 30	KH	NCAIC	UNV-D22	HSG	P3RAF		S	WH	TRM	N/A	QS
Round Trimless, IC Rated	1075	P3RA-15L2M	27 or 30	KH	NCAIC	UNV-D22	HSG	P3RAL		S	WH	TRM	P3RA-SPAK	QS
Square Trimmed, IC Rated	1150	P3SA-15L2M	27 or 30	KH	NCAIC	UNV-D22	HSG	P3SAF		S	WH	TRM	N/A	QS
Square Trimless, IC Rated	1150	P3SA-15L2M	27 or 30	KH	NCAIC	UNV-D22	HSG	P3SAL		S	WH	TRM	P3SA-SPAK	QS

NOTES

- Nailer bars are included. Butterfly brackets and channel bars are extra:

- ° PFBK-CB27 (27")
- ° PFBK-CB32 (32")
- ° PFBK-CB52 (52")

4.5" BeveLED® 2.2 Primary® NXT

 Dry/Damp/Wet Location Listed Under Covered Ceilings

Primary NXT comes with a Tri-Mode integral driver with 1% dimming. Tri-Mode drivers are compatible with:

1. 0-10V dimming with all voltages from 120V-277V
2. Forward phase or reverse phase dimming with 120V



Adjustable Downlight

Comes in round or square, trimmed or trimless with a white finish.

Ships with 20° or 55° TIR optic installed; replacement optics for 25° and 40° beams are available on spec sheets with standard lead times.

Fixture Type	Delivered Lumens	Housing						Trim					Accessory	 Quick Ship
		Wattage	Select Color Temp	High CRI	Housing	Voltage & Driver	HSG	Trim Style	Select Optic	Solite Lens	Trim Finish	Trim		
Round Trimmed, 15W	1150 - 1475	PB4R-15L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4RAF	T20 or T55	S	WH-WH	TRM	N/A	QS
Round Trimless, 15W	1150 - 1475	PB4R-15L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4RAL	T20 or T55	S	WH	TRM	PB4R-SPAK	QS
Square Trimmed, 15W	1150 - 1475	PB4S-15L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4SAF	T20 or T55	S	WH-WH	TRM	N/A	QS
Square Trimless, 15W	1150 - 1475	PB4S-15L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4SAL	T20 or T55	S	WH	TRM	PB4S-SPAK	QS
Round Trimmed, 20W	1550 - 2025	PB4R-20L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4RAF	T20 or T55	S	WH-WH	TRM	N/A	QS
Round Trimless, 20W	1550 - 2025	PB4R-20L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4RAL	T20 or T55	S	WH	TRM	PB4R-SPAK	QS
Square Trimmed, 20W	1550 - 2025	PB4S-20L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4SAF	T20 or T55	S	WH-WH	TRM	N/A	QS
Square Trimless, 20W	1550 - 2025	PB4S-20L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4SAL	T20 or T55	S	WH	TRM	PB4S-SPAK	QS



Wall Wash

Comes in round or square, trimmed or trimless with a white finish.

Fixture Type	Delivered Lumens	Housing						Trim					Accessory	 Quick Ship
		Wattage	Select Color Temp	High CRI	Housing	Voltage & Driver	HSG	Trim Style	Optic	Wall Wash	Trim Finish	Trim		
Round Trimmed, 15W	1000 - 1175	PB4R-15L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4RWF	W2	D2	WH-WH	TRM	N/A	QS
Round Trimless, 15W	1000 - 1175	PB4R-15L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4RWL	W2	D2	WH	TRM	PB4R-SPAK	QS
Square Trimmed, 15W	925 - 1175	PB4S-15L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4SWF	W2	D2	WH-WH	TRM	N/A	QS
Square Trimless, 15W	925 - 1175	PB4S-15L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4SWL	W2	D2	WH	TRM	PB4S-SPAK	QS
Round Trimmed, 20W	1375 - 1600	PB4R-20L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4RWF	W2	D2	WH-WH	TRM	N/A	QS
Round Trimless, 20W	1375 - 1600	PB4R-20L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4RWL	W2	D2	WH	TRM	PB4R-SPAK	QS
Square Trimmed, 20W	1350 - 1575	PB4S-20L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4SWF	W2	D2	WH-WH	TRM	N/A	QS
Square Trimless, 20W	1350 - 1575	PB4S-20L3M	30 or 35	KH	NCEC	UNV-D31	HSG	PB4SWL	W2	D2	WH	TRM	PB4S-SPAK	QS



Primary® NXT Quick Ship Program

Ships within 10 Days

Tier 1
Budget Friendly



USAI[®]
Lighting

USAI LIGHTING HEADQUARTERS
1126 River Road
New Windsor, NY 12553
T: 845-565-8500
info@usailighting.com

©2025 USAI Lighting All Rights Reserved.
USAI, BeveLED, BeveLED Mini, Primary,
and Classic White are registered trademarks
of USAI, LLC. All designs protected by copyright
Covered by US Patents. CA-064E